

RACE NO

Three stacked empty boxes for RACE NO, CAT, and EVENT.

CAT

EVENT



# TEAM MANAGER CHECK LIST - FORM 2A 2019

ENTRANT

Empty box for ENTRANT name

VEHICLE NAME

Empty box for VEHICLE NAME

\*Numbers below refer to Vehicle Specifications or Event Manual

ITEM	*REF	
<b>To maintain the safety of all Team Riders:</b>		
1	Riders are within vehicle structures.	1.4.2c, 2.2.1a+b, 4.2, 4.7.3 <input type="checkbox"/>
2	Riders safe from drive line [clothing, hair, hands, legs --- wheels, spokes, chain, rollers].	2.2.9, 4.1, 6.1.3 <input type="checkbox"/>
3	Lap seat belt mounts and seat shape enable correct belt placement.	5.2 [5.2.7] <input type="checkbox"/>
4	Shoulder seat belt mounts or guides are level with Riders' shoulders or higher.	5.2.6a <input type="checkbox"/>
5	Seat belt to be adjusted for each Rider with lap belt kept on pelvis.	5.1, 5.2 <input type="checkbox"/>
6	Certified helmet fitted correctly with no devices mounted on it.	2.3.5, 7.1.4, E.M. <input type="checkbox"/>
7	There is airflow for Rider ventilation and windscreen defogging.	2.3.6 <input type="checkbox"/>
8	Bodywork, canopies, vehicle structures maintained in safe condition.	2.2.2+3+5+8, 2.3.1+2+3 <input type="checkbox"/>
9	Side impact protection covers shoulders, torso, hips, legs to knees of Riders.	4.3, 4.7.5 <input type="checkbox"/>
10	Head restraint system protects Riders.	4.4 <input type="checkbox"/>
11	Inside structures (steering, brakes, frame, panels) safe and with clearance	2.2.1d, 2.3.3c, 6.1.4+5, 6.3.1 <input type="checkbox"/>
12	Closed Canopy front wheel guards minimize wheel borne debris inside canopy	2.2.9 <input type="checkbox"/>
<b>For their development, every rider should:</b>		
13	Complete a Roll-Over test to self validate their harness wearing and vehicle's protections	E.M. <input type="checkbox"/>
14	Have practised, and be able to perform, the 4 X 4.2m Slalom Test.	E.M. <input type="checkbox"/>
<b>Every rider must:</b>		
15	For Closed Canopy vehicle, have the head room to meet the Roller Test indicators.	1.4.2c, 2.3.4, 4.9.3, 8.3 <input type="checkbox"/>
16	For Open Cockpit vehicle, have 100mm minimum clearance above their helmet to the Rider Rollover Protection Structure and Cockpit Overhead Protection.	4.8.2b, 4.10.4 <input type="checkbox"/>
17	Be able to see the ground 5m ahead when in their riding position.	2.4.3 <input type="checkbox"/>
18	Be able to sight overtaking traffic in their mirrors.	6.4 <input type="checkbox"/>
<b>Vehicle construction:</b>		
19	Maintain vehicle to meet 2019 Specifications during Events and other uses.	1.4, 2.1, 2.2.1b, 2.2.8, 6.2.1, <input type="checkbox"/>
20	Vehicle meets Cockpit Overhead Protection requirements for all Riders.	4.6.2, 4.7.6, 4.9.1, 4.10 <input type="checkbox"/>
21	Specified Foam above all Rider's positions in Closed Canopy vehicle.	4.9.2, 8.4 <input type="checkbox"/>
22	Open Cockpit vehicle is 500mm wide at all Riders' shoulders.	4.8.1 <input type="checkbox"/>
<b>Attachments:</b>		
23	Speedo installed, operational and visible to Riders.	7.3 <input type="checkbox"/>
24	Red LED tail light correctly positioned and set to steady. [Headlight for night Events]	7.1.3 [7.0] <input type="checkbox"/>
25	Batteries mounted securely and not liquid type	2.2.4 <input type="checkbox"/>
<b>Prohibitions:</b>		
26	Window treatments and bodywork are not in the way of Riders' vision.	2.4.1, 2.4.2 <input type="checkbox"/>
27	Excessive seat padding not being used.	5.1.3 <input type="checkbox"/>

NAME OF TEAM MANAGER

Empty box for NAME OF TEAM MANAGER

SIGNATURE

Empty box for SIGNATURE

DATE

Empty box for DATE, pre-filled with \_\_\_\_ / \_\_\_\_ / 2019